

# JOHNSON MANUFACTURING COMPANY

## Safety Data Sheet

To comply with 29CFR 1910.1200  
OSHA's Hazard Communication Standard

### Activated Rosin Flux, 27-00

---

#### 1. PRODUCT AND COMPANY INFORMATION

---

Johnson Manufacturing Company  
114 Lost Grove Road  
Princeton IA 52768

Emergency Telephone 1-(563)-289-5123  
CHEMTREC AFTER HOURS 1-(800)-424-9300  
Revised 1/1/2018 by JMC Product Safety

#### 2. HAZARD IDENTIFICATION

---

##### GHS Classification:

skin sens 1  
Eye Irrit. 2  
Flamm liq 2  
acute tox 4  
skin irr 2



##### GHS Label Elements:

**ETHANOL & GUM ROSIN**  
**DANGER**

**H Codes:** H302, H225, H315, H317, H319, H335, H336

Harmful if swallowed  
May be harmful if inhaled  
May cause an allergic skin reaction  
Causes serious eye irritation  
Highly flammable liquid & vapor  
May cause drowsiness or dizziness

##### **P Codes:**

P264, 272, 280, 321, 210, 233, 240, 241, 242, 243, 403+233, 370+378, 303+361+353, 501, 312, 261, 271, 280, 332+313, 302+352, 363, 304+340, 405, 305+351+338+310, 337+313, 270, 301+313, 330, 362, 333+313

Avoid breathing dust/mist/vapors/fumes/spray. Do not get in eyes, on skin, or on clothing. Use in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not breathe dust/fume/gas/mist/vapor/spray. Do not eat, drink or smoke when using this product. Keep away from heat, sparks or open flame – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion proof electrical/ventilating/lighting and equipment. Use only non-sparking tools. Take precautionary measures against static discharge. In case of fire use foam or dry chemical for extinction. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with soap & water. Get medical advice/attention if you feel unwell or if a skin irritation or rash occurs. IF INHALED: Remove victim to to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor. Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed compatible container in cool dry place. Avoid release to the environment. Dispose of contents/container in accordance with specified local/regional/national/international regulations for disposal. Keep out of the reach of children. Read label and SDS prior to use.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

Hazardous Component	CAS #	OSHA TWA	ACIGH TWA	Other limits	%
Ethanol	64-17-5	1000 ppm	1000 ppm	NE	
Rosin	8050-09-7	NE	NE	NE	

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.  
An ingredient marked with an asterisk(\*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

#### 4. FIRST AID MEASURES

---

**Signs and symptoms of exposure:** Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting,

cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

**Medical conditions aggravated by exposure:** Skin, kidney and respiratory conditions.

**Emergency first aid procedures:**

Skin: Flush with water immediately - Seek medical attention if necessary

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical attention. Never give anything by mouth to an unconscious person

Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention

## 5. FIREFIGHTING MEASURES

---

**Extinguishing media:** dry chemical.

**Special fire fighting procedures:** use self sustaining respiratory suit.

**Unusual Fire and Explosion Hazards:** May release carbon monoxide, carbon dioxide. Pyrolysis of Rosin yields Formaldehyde, OSHA & ACGIH TWA = 0.1mg/M3

## 6. ACCIDENTAL RELEASE MEASURES

---

**Methods and materials:** Flush into chemical sewer or soak up with a suitable absorbent. Wear adequate protection as described in section 8.

**Environmental Precautions:** Avoid release to the environment. Collect spillage.

## 7. HANDLING & STORAGE

---

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Occupational Exposure Limit Values:** See section 3.

Respiratory Protection (type): Organic Acid mask required for fumes above TWA.

Ventilation: Local Exhaust preferred Special: NE

Mechanical: OK Other: NE

Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Boiling Point: 78 C

Specific Gravity: 0.85

Vapor Pressure (mm Hg): NE

Melting Point: NE

Vapor Density: 1.6

Evaporation Rate: 1.6 (butyl acetate=1)

Solubility in water: negligible

pH: NE

Flash Point: 61 F (TOC)

Flammable Limits: lel: 4.3% uel: 19%

Appearance and odor: Amber Liquid, alcohol odor.

## 10. STABILITY AND REACTIVITY

---

**Stability :** STABLE Conditions to avoid : none

**Incompatibility (materials to avoid):** strong bases & acids, oxidizers, sulfides, halogens.

**Hazardous Decomposition or Byproducts (incomplete combustion):** May release carbon monoxide, carbon dioxide. Pyrolysis of Rosin yields Formaldehyde, OSHA & ACGIH TWA = 0.1mg/M3

**Hazardous Polymerization:** WILL NOT OCCUR Conditions to avoid: none

## 11. TOXICOLOGICAL INFORMATION

---

**Routes of entry:** Inhalation: yes Skin: no Ingestion: yes

**Health Hazards (acute and chronic):** Contact with material, mist or fumes may cause skin, eye and respiratory tract irritation. Ingestion may cause digestive tract irritation. Dense vapor concentrations may present asphyxiation hazard. Excessive inhalation and ingestion may result in eye effects including blindness. Gross inhalation and ingestion may be toxic and can result in death. May be mutagenic in lab animals. Chronic exposures can result in liver, nervous and respiratory system effects. Studies show that potential health risks may vary by individual. Always minimize exposure as a precaution.

**Carcinogenicity:** not determined NPT? no IARC Monographs? no

## 12. ECOLOGICAL INFORMATION

---

Toxicity: NE  
Bio-accumulative Potential: NE  
PBT & vPvB Assessment: NE

Persistence & Degradability: NE  
Mobility in Soil: NE  
Other Adverse Effects: NE

## 13. DISPOSAL CONSIDERATIONS

---

**Waste Disposal Method:** dispose of in accordance with all local state and federal regulations

**Other Precautions:** Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

## 14. TRANSPORT INFORMATION

---

**DOT Classification:** UN1170, Ethanol, 3, PG II

**Marine Pollutant:** NE

## 15. REGULATORY INFORMATION

---

NFPA Classification (NFPA 325M, 8<sup>th</sup> edition)(Health, Flammability, Reactivity): 1-3-0

This product can expose you to chemicals including ethylene oxide, which is known to the state of California to cause cancer and/or birth defects or reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## 16. OTHER INFORMATION

---

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING nor does JOHNSON MANUFACTURING assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

---

NE = not established NA = not applicable

Form 303.70 Rev.E