

# JOHNSON MANUFACTURING COMPANY

## Safety Data Sheet

To comply with 29CFR 1910.1200  
OSHA's Hazard Communication Standard

### C-7 Flux

---

#### 1. PRODUCT AND COMPANY INFORMATION

---

Johnson Manufacturing Company  
114 Lost Grove Road  
Princeton IA 52768

Emergency Telephone 1-(563)-289-5123  
CHEMTREC AFTER HOURS 1-(800)-424-9300  
Revised 1/1/2018 by JMC Product Safety

#### 2. HAZARD IDENTIFICATION

---

##### GHS Classification:

Eye Irrit. 2  
skin sens 1  
acute tox 5



##### GHS Label Elements:

##### **GUM ROSIN & GLYCOL ETHERS WARNING**

##### **H Codes:** H319, H317, H303, H333

May be harmful if swallowed  
May be harmful if inhaled  
May causes eye irritation  
May cause an allergic skin reaction

##### **P Codes:**

P264, 280, 501, 261, 272, 302+352, 333+313, 321, 363

Avoid breathing mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation use respiratory protection. Do not breathe dust/fume/gas/mist/vapor/spray. Do not eat, drink or smoke when using this product. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Immediately call a POISON CENTER/Doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. IF INHALED: Remove victim to to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call POISON CENTER/Doctor. Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed compatible container in cool dry place. Avoid release to the environment. Dispose of contents/container in accordance with specified local/regional/national/international regulations for disposal. Keep out of the reach of children. Read label and SDS prior to use.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

Hazardous Component	CAS #	OSHA TWA	ACIGH TWA	Other limits	%
Rosin	8050-09-7	NE	NE	NE	
+ Ethylene Glycol Phenyl Ether	122-99-6	NE	NE	NE	26

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.  
An ingredient marked with an asterisk(\*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

#### 4. FIRST AID MEASURES

---

**Signs and symptoms of exposure:** Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

**Medical conditions aggravated by exposure:** Skin, kidney and respiratory conditions.

##### **Emergency first aid procedures:**

Skin: Flush with water immediately - Seek medical attention if necessary  
Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: DO NOT induce vomiting, drink large amounts of water - seek medical attention. Never give anything by mouth to an unconscious person  
Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention

## 5. FIREFIGHTING MEASURES

---

**Extinguishing media:** dry chemical. **Special fire fighting procedures:** use self sustaining respiratory suit. **Unusual Fire and Explosion Hazards:** May release carbon dioxide, carbon monoxide, sulfur. Pyrolysis of Rosin Core Solder yields Formaldehyde, OSHA & ACGIH TWA = 0.1mg/M3

## 6. ACCIDENTAL RELEASE MEASURES

---

**Methods and materials:** Flush into chemical sewer or soak up with a suitable absorbent. Wear adequate protection as described in section 8.  
**Environmental Precautions:** Avoid release to the environment. Collect spillage.

## 7. HANDLING & STORAGE

---

Wash thoroughly after use. Wash contaminated clothing before reuse. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Keep out of the reach of children. Read label and SDS prior to use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**Occupational Exposure Limit Values:** See section 3.  
Respiratory Protection (type): Organic vapor for fumes above TWA.  
Ventilation: Local Exhaust preferred Special: NE  
Mechanical: OK Other: NE  
Protective Gloves: plastic or rubber Eye Protection: Goggles or face shield  
Other Protective Clothing or Equipment: as required to avoid contact.  
Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Boiling Point: NE Specific Gravity: > 1.0  
Vapor Pressure (mm Hg): NE Melting Point: 410 F  
Vapor Density: NE Evaporation Rate: <1 (butyl acetate=1)  
Solubility in water: partial pH: NE  
Flash Point: 125 F (TOC) Flammable Limits: lel: NE uel: NE  
Appearance and odor: Amber Paste, ethereal odor.

## 10. STABILITY AND REACTIVITY

---

**Stability :** STABLE Conditions to avoid : none

**Incompatibility (materials to avoid):** strong bases & acids, oxidizers, sulfides, halogens.  
**Hazardous Decomposition or Byproducts (incomplete combustion):** Carbon dioxide, carbon monoxide, sulfur. Pyrolysis of Rosin Core Solder yields Formaldehyde, OSHA & ACGIH TWA = 0.1mg/M3  
**Hazardous Polymerization:** WILL NOT OCCUR Conditions to avoid: none

## 11. TOXICOLOGICAL INFORMATION

---

**Routes of entry:** Inhalation: yes Skin: yes Ingestion: yes

**Health Hazards (acute and chronic):** Contact with dust may cause eye and respiratory tract irritation. Chronic and or repeated inhalation of dust and or fumes from combustion, may cause fibrosis of the lungs. Toxicity by ingestion is low. Treat as a nuisance dust (OSHA,ACGIH TWA=10mg/M3). Studies show that potential health risks vary by individual. Always minimize exposure as a precaution.

**Carcinogenicity:** not determined NPT? no IARC Monographs? no

## 12. ECOLOGICAL INFORMATION

---

**Toxicity:** NE **Persistence & Degradability:** NE  
**Bio-accumulative Potential:** NE **Mobility in Soil:** NE  
**PBT & vPvB Assessment:** NE **Other Adverse Effects:** NE

### **13. DISPOSAL CONSIDERATIONS**

---

**Waste Disposal Method:** dispose of in accordance with all local state and federal regulations

**Other Precautions:** Avoid skin & eye contact, inhalation & ingestion of fumes and material. Wash contaminated clothing before reuse. Keep away from children.

### **14. TRANSPORT INFORMATION**

---

**DOT Classification:** Non-Hazardous

**Marine Pollutant:** NE

### **15. REGULATORY INFORMATION**

---

NFPA Classification (NFPA 325M, 8<sup>th</sup> edition)(Health, Flammability, Reactivity): 1-1-0

### **16. OTHER INFORMATION**

---

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING nor does JOHNSON MANUFACTURING assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

---

NE = not established NA = not applicable

Form 303.499 Rev.D